

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Powerball

PRODUCT USE: Concentrated degreaser

MANUFACTURED FOR: Warsaw Chemical Holdings LLC.
P.O. Box 858
Warsaw, IN 46581

INFORMATION PHONE: Tel: 1-800-548-3396
Fax: 1-574-267-3884

EMERGENCY PHONE: INFOTRAC
1-800-535-5053 USA & Canada
352-323-3500 International

SECTION 2 - HAZARD(S) IDENTIFICATION

CLASSIFICATION: Skin Corrosion: Category 1C
Eye Damage: Category 2A
Skin Sensitization: Category 1

PICTOGRAMS:



GHS ELEMENTS:

SIGNAL WORD: Danger

HAZARD STATEMENT(S): H314 | Causes severe skin burns and eye damage.
H319 | Causes serious eye irritation.
H317 | May cause an allergic skin reaction.

PRECAUTIONARY STATEMENT(S): P260 | Do not breathe dust/fume/gas/mist/vapours/spray.
P261 | Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 | Wash any exposed body parts thoroughly after handling.
P272 | Contaminated work clothing should not be allowed out of the workplace.
P280 | Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P330 + P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302 + P352 | IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 | Immediately call a POISON CENTER or doctor/physician.
P321 | Specific treatment (see supplemental first aid instruction on this label)

if immediate administration of antidote/specific measures/cleansing agent/immediate measures is/are appropriate/required).
P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 | If eye irritation persists: Get medical advice/attention.
P405 | Store locked up.
P501 | Dispose of contents/container to appropriate waste disposal entity in accordance with local/regional/national/international regulation.

ADDITIONAL PRECAUTIONS: None Known

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS #	FUNCTIONAL PURPOSE	PERCENT
Sodium Hydroxide 50%	1310-73-2	pH Adjustment	10 - 20%
2-Butoxyethanol	111-76-2	Solvent	5 - 10%
Sodium Xylenesulfonate	1300-72-7	Surfactant	1 - 5%
Sodium Metasilicate Pentahydrate	10213-79-3	Alkaline Builder	1 - 5%
Tetrasodium EDTA	64-02-8	Water Softener	1 - 5%
Surfactant	68130-47-2	Surfactant	1 - 5%
Alcohols, ethoxylated	not available	Surfactant	< 1.0%
Quaternary Ammonium compound, Coco	68071-91-0	Surfactant	< 1.0%
Nonylphenol ethoxylate	127087-87-0	Surfactant	< 1.0%
Acid Violet 54	Not Available	Colorant	< 1.0%
Direct Blue 199	12222-04-7	Colorant	< 1.0%
Chloromethylisothiazolone	55965-84-9	Preservative	< 1.0%

The chemical identity of some or all components is confidential business information (trade secret) and is being withheld as permitted by 29CFR19191200 (i). No other ingredients known to be hazardous.

SECTION 4 - FIRST AID MEASURES

EYES: Check for and remove contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

SKIN: Wash skin surfaces thoroughly after contact. Wash clothing and clean shoes thoroughly before reuse. Get medical attention if irritation develops.

INHALATION: Move exposed person to fresh air. If breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen clothing. Get medical attention immediately.

INGESTION: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

GENERAL: Physicians: No specific treatment. Treat symptomatically. Contact poison treatment specialist if large quantities have been inhaled or ingested.

See Section 11 for exposure symptoms.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABILITY:	In a fire or if heated, a pressure increase will occur and the container may burst.
EXTINGUISHING MEDIA:	Use an extinguishing agent suitable for the surrounding fire.
PROTECTIVE EQUIPMENT:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated in positive pressure mode.
ADDITIONAL INFORMATION:	Thermal decomposition products-carbon monoxide, sulfur oxides, metal oxide/oxides, halogenated compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:	No action should be taken involving individual risk or without suitable training. Isolate area. Avoid contact with material. Do not breathe vapors. Provide adequate ventilation. Wear proper personal protective equipment.
ENVIRONMENTAL:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform relevant authorities if the product reaches sewers, waterways or soil.
CONTAINMENT/CLEANUP:	Stop leak if without risk. Move containers from spill area. Contain or absorb with inert dry material. Dispose of according to local regulations. See Section 1 for emergency contact information and 13 for waste disposal.

SECTION 7 - HANDLING AND STORAGE

SAFE HANDLING:	Wear appropriate personal protective equipment (see Section 8). Eating drinking and smoking should be prohibited. Do not get into eyes or on skin. Do not ingest. Keep containers tightly closed. Do not reuse container.
SAFE STORAGE:	Store in accordance with local regulations. Store in original container away from foods, drink and incompatible materials. Keep container tightly closed. Do not store unlabeled. Use appropriate containment.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:	Apply technical measures to comply with occupational exposure limits. Mechanical ventilation, eyewash stations, showers where necessary.
EYE PROTECTION:	Safety eye-wear/face shield complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
RESPIRATORY PROTECTION:	Use a properly fitted air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates necessity. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product & the safe working limits of the chosen respirator.
HAND PROTECTION:	Chemical resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

SKIN PROTECTION:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

COMPONENT:	ACGIH TWA ppm	OSHA/NIOSH STEL ppm	OSHA/ACGIH STEL mg/m3
Sodium Hydroxide 50%	2.00	None	None
2-Butoxyethanol	20.00	None	None
Sodium Xylenesulfonate	None	None	None
Sodium Metasilicate Pentahydrate	None	None	None
Tetrasodium EDTA	None	None	15.00
Surfactant	None	None	1.00
Alcohols, ethoxylated	None	None	None
Quaternary Ammonium compound, Coco	72.00	None	None
Nonylphenol ethoxylate	10.00	None	None
Acid Violet 54	None	None	None
Direct Blue 199	None	None	None
Chloromethylisothiazolone	None	None	None

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid	UPPER EXPLOSIVE LIMITS:	NA
COLOR:	Purple	LOWER EXPLOSIVE LIMITS:	NA
ODOR:	Butyl	VAPOR PRESSURE:	NA
ODOR THRESHOLD:	NA	VAPOR DENSITY:	NA
PH:	11.5 - 14.0	RELATIVE DENSITY:	NA
MELTING POINT:	NA	SOLUBILITY:	Completely Water Soluble
FREEZING POINT:	23.00 F	PARTITION COEFFICIENT:	NA
BOILING POINT:	NA	AUTO-IGNITION TEMPERATURE:	NA
FLASH PT METHOD:	NA	DECOMPOSITION TEMPERATURE:	NA
FLASH POINT:	NA	SPECIFIC GRAVITY:	1.07000
EVAPORATION RATE:	NA	% VOLATILE:	2.60000
FLAMMABILITY:	Nonflammable	VISCOSITY (cst):	NA

SECTION 10 - STABILITY AND REACTIVITY

REACTIVITY:	HAZARDOUS DECOMPOSITION PRODUCTS
CHEMICAL STABILITY:	Stable under normal conditions.
POSSIBILITY OF HAZARDOUS REACTIONS:	Non-reactive.

CONDITIONS TO AVOID: Excessive heat or open flame.

INCOMPATIBLE MATERIALS: Avoid contact with acidic materials and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Under normal conditions, none are known.

SECTION 11 - TOXICOLOGICAL INFORMATION

ROUTES OF ENTRY: Inhalation X Absorption X Ingestion

ACUTE EXPOSURE HAZARDS:

EYE CONTACT: Irritation, stinging, redness, burns.

DERMAL: Irritation, burns upon prolonged exposure.

ORAL: Nausea, vomiting.

INHALATION: No expected route of entry. Irritation.

2-Butoxyethanol (CAS No. 111-76-2)
Oral LD50: Rat 470 mg/kg

Sodium Xylenesulfonate (CAS No. 1300-72-7)
Oral LD50: Rat 5 g/kg

Sodium Metasilicate Pentahydrate (CAS No. 10213-79-3)
Oral LD50: Rat 1152-1349 mg

Tetrasodium EDTA (CAS No. 64-02-8)
Oral LD50: 630-1,260mg/kg, rat

Surfactant (CAS No. 68130-47-2)
Oral LD50: Rat 3.95 mg/kg

Alcohols, ethoxylated (CAS No. not available)
Oral LD50: Greater than 50 mg/kg
Dermal LD50: Greater than 200 mg/kg

Nonylphenol ethoxylate (CAS No. 127087-87-0)
Oral LD50: Rat 1600 mg/kg

Chloromethylisothiazolone (CAS No. 55965-84-9)
Oral LD50: 66mg/kg rabbit
Dermal LD50: 141mg/kg rat

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY: No data available.

PERSISTENCE & DEGRADABILITY: No data available.
 BIOACCUMULATIVE POTENTIAL: No data available.
 MOBILITY IN SOIL: No data available.
 OTHER ADVERSE EFFECTS: No data available.

Sodium Hydroxide 50% (CAS No. 1310-73-2)
 Fish LC50: 144mg/L, 96h guppy
 2-Butoxyethanol (CAS No. 111-76-2)
 Fish LC50: 1250mg/L, 96h, Inland Solverside
 Crustacean LC50: Daphnia 1818 mg/L 24h
 Sodium Xylenesulfonate (CAS No. 1300-72-7)
 Fish LC50: Minnow 1000 mg/L 96h
 Sodium Metasilicate Pentahydrate (CAS No. 10213-79-3)
 Fish LC50: Danio Rerio (Zebra Fish) 210 mg/L 96h
 Tetrasodium EDTA (CAS No. 64-02-8)
 Fish LC50: 410mg/kg, 96h, bluegill
 Surfactant (CAS No. 68130-47-2)
 Fish LC50: Rainbow trout 5.5 mg/kg 96h
 Chloromethylisothiazolone (CAS No. 55965-84-9)
 Fish LC50: 0.22mg/L 96h trout
 Crustacean LC50: 6.76mg/L 48h daphnia

SECTION 13 - DISPOSAL CONSIDERATION

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of the product may change the waste management options. Waste generators must decide if discarded material is a hazardous waste. State and local disposal regulations may differ from federal disposal definitions. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14 - TRANSPORT INFORMATION

DOT (US)

UN NUMBER: UN1760
 SHIPPING NAME: Corrosive Liquids, N.O.S.
 TECHNICAL NAME: (Sodium Hydroxide, Silicates)
 HAZARD CLASS: 8
 PACKAGING GROUP: II

SECTION 15 - REGULATORY INFORMATION

SARA 313 COMPONENTS	CAS NO.	% LESS THAN
2-Butoxyethanol	111-76-2	5 - 10%

CALIFORNIA PROP. 65 COMPONENTS

CAS NO.

% LESS THAN

2-Butoxyethanol
Tetrasodium EDTA
Quaternary Ammonium compound, Coco
Nonylphenol ethoxylate

111-76-2
64-02-8
68071-91-0
127087-87-0

5 - 10%
1 - 5%
< 1.0%
< 1.0%

RQ 1,000#

This product can expose you to Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm..

contains Nitrilo Acetic Acid <0.3% max and arsenic (max 1ppm) as contaminants or bi-products which are known to the State of

California to cause cancer or reproductive toxicity as listed under Prop. 65 State Drinking Water and Toxic Enforcement Act.

1,4Dioxane (0.1%) known by the state of California to cause cancer, Ethylene Oxide (0.1%) known by the state of California to cause cancer, developmental and reproductive toxicity.

127087-87-0 Nonylphenol polyethylene glycol ether 90 - 100 %

25322-68-3 Polyethylene glycol 1 - 5 %

123-91-1 1,4-Dioxane 0 - 0.1 %

64-19-7 Acetic acid 0 - 0.1 %

75-21-8 Ethylene oxide 0 - 0.1 %

RTK: MA, PA, NJ,

WARNING! This product contains a chemical known to the State of California to cause cancer birth defects or other reproductive harm.

123-91-1 1,4-Dioxane 0 - 0.1 %

64-19-7 Acetic acid 0 - 0.1 %

75-21-8 Ethylene oxide 0 - 0.1 %

SECTION 16 - OTHER INFORMATION


HAZARDOUS MATERIAL INFORMATION SYSTEM (U.S.A.)

Health Hazard	2
Fire Hazard	0
Reactivity	0
Personal Protection	C

- A Safety Glasses
- B Safety Glasses, Gloves
- C Safety Glasses, Gloves, Apron
- D Face Shield, Gloves, Apron
- E Safety Glasses, Gloves, Dust Respirator
- F Safety Glasses, Gloves, Apron, Dust Respirator
- G Safety Glasses, Gloves, Vapor Respirator
- H Splash Goggles, Gloves, Apron, Dust & Vapor Respirator
- I Safety Glasses, Gloves, Dust & Vapor Respirator
- J Splash Goggles, Gloves, Apron, Dust & Vapor Respirator
- K Airline Hood or Mask, Gloves, Full Suit, Boots
- X Consult your supervisor for special handling directions

Caution: HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks and 4 representing significant hazards or risks.

NATIONAL FIRE PROTECTION ASSOCIATION (U.S.A.)





Safety Data Sheet

Powerball

Page 8 of 8

Version: 1.0021
Revision Date: 02/08/2019
Print Date: 04/02/2021

NFPA warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health, and reactivity hazards of chemicals.

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act of 1970 and shall not be used for any other purpose. Use or dissemination of all or any part of this information can be grounds for legal action.

To the best of our knowledge, the information provided in this Safety Data Sheet is accurate as of the date of its issue. However, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE. The information this Safety Data Sheet contains is being given to that material when combined with other material(s) or when used otherwise than as described herein.

In all cases, it is the responsibility of the user to determine the applicability of such information and recommendations and the suitability of any product for its own particular purpose. All materials may represent unknown hazards and should be used with caution.